


室内灯具光度数据

实测参数: U:232.26V I:0.1799A P:22.347W PF:0.5349 Freq:49.99Hz 实检光通:1214.41x1 lm					
灯具名称: W2923LED		灯具类型:		灯具重量:	
灯具规格: P-W2923LED-3x7W2718-CI50012R90-YML100		外型尺寸:		测试编号:	
制造厂商:		发光口面:		遮光角:	

光源数据		光度数据				光效: 54.34 lm/W
型号	CLU7A3 0403	峰值光强(cd)	8699	S/MH(C0/180)	0.33	
标称功率(W)	3x7W	灯具效率(%)	100.0	S/MH(C90/270)	0.35	
额定电源电压(V)	220.0	总光通量(lm)	1214.4	η UP,DN(C0-180)	0.2,48.5	
额定光通量(lm)	1214.41	CIE分类	直接	η UP,DN(C180-360)	0.1,51.2	
灯具内光源数(只)	1	上射光通比(%)	0.3	CIBSE SHR NOM	0.00	
实测电源电压(V)	220.2	下射光通比(%)	99.7	CIBSE SHR MAX	1.00	



C角度范围: 0度 - 360度
C角度间隔: 90.0度
测试速度: 快速
环境温度:25.3℃
测试人员:Xie Bi
测试日期:2024-09-03

γ角度范围: 0度 - 180度
γ角度间隔: 0.5度
测试系统: 远方(EVERFINE)GO-2000A_V1系统 V2.00.417
环境湿度:65.0%
测试距离:6.810米 [K=1.0000]
备注:

灯具环带光通量

环带光通量:


γ	C0	C90	C180	C270					γ(°)	Φ环	Φ总	%lum, lamp
10	4335	3872	4204	4438					0- 10	587.7	587.7	48.4, 48.4
20	539.6	454.5	531.7	581.0					10- 20	509.6	1097	90.4, 90.4
30	65.50	61.95	63.74	67.06					20- 30	82.11	1179	97.1, 97.1
40	17.23	14.69	16.06	17.93					30- 40	22.25	1202	98.9, 98.9
50	4.243	4.024	4.417	5.316					40- 50	6.747	1208	99.5, 99.5
60	0.7196	0.5073	0.6620	0.8883					50- 60	1.953	1210	99.7, 99.7
70	0	0	0	0					60- 70	0.1849	1211	99.7, 99.7
80	0	0	0	0					70- 80	0	1211	99.7, 99.7
90	0	0	0	0					80- 90	0	1211	99.7, 99.7
100	0	0	0	0					90-100	0	1211	99.7, 99.7
110	0	0	0	0					100-110	0	1211	99.7, 99.7
120	0	0	0.0087	0.0052					110-120	0.0008	1211	99.7, 99.7
130	0.0104	0.0227	0.0384	0.0349					120-130	0.0099	1211	99.7, 99.7
140	0.2195	0.3092	0.1118	0.1098					130-140	0.0607	1211	99.7, 99.7
150	1.874	2.131	0.7818	0.7649					140-150	0.3797	1211	99.7, 99.7
160	5.726	5.792	3.500	3.348					150-160	1.289	1212	99.8, 99.8
170	6.636	6.795	5.699	5.609					160-170	1.599	1214	100, 100
180	5.552	5.735	5.540	5.742					170-180	0.5654	1214	100, 100
单位:°	光强:cd									单位:lm		

C角度范围: 0度 - 360度
C角度间隔: 90.0度
测试速度: 快速
环境温度:25.3℃
测试人员:Xie Bi
测试日期:2024-09-03

γ角度范围: 0度 - 180度
γ角度间隔: 0.5度
测试系统: 远方 (EVERFINE) GO-2000A_V1系统 V2.00.417
环境湿度:65.0%
测试距离:6.810米 [K=1.0000]
备注:

灯具亮度限制曲线

实测参数: U:232.26V I:0.1799A P:22.347W PF:0.5349 Freq:49.99Hz 实检光通:1214.41x1 lm		
灯具名称: W2923LED	灯具类型:	灯具重量:
灯具规格: P-W2923LED-3x7W2718-CI50012R90-YML100	外型尺寸:	测试编号:
制造厂商:	发光口面:	遮光角:



平均亮度值 cd/(m2)		
γ (°)	C0/180	C90/270
85	0	0
80	0	0
75	0	0
70	0	0
65	40	0
60	156	110
55	385	281
50	718	680
45	1306	1061


C角度范围: 0度 - 360度
C角度间隔: 90.0度
测试速度: 快速
环境温度:25.3℃
测试人员:Xie Bi
测试日期:2024-09-03

γ角度范围: 0度 - 180度
γ角度间隔: 0.5度
测试系统: 远方 (EVERFINE) GO-2000A_V1系统 V2.00.417
环境湿度:65.0%
测试距离:6.810米 [K=1.0000]
备注:

工作面利用系数和灯具概算曲线

实测参数: U:232.26V I:0.1799A P:22.347W PF:0.5349 Freq:49.99Hz 实检光通:1214.41x1 lm		
灯具名称: W2923LED	灯具类型:	灯具重量:
灯具规格: P-W2923LED-3x7W2718-CI50012R90-YML100	外型尺寸:	测试编号:
制造厂商:	发光口面:	遮光角:

顶棚	80%			70%			50%			30%			10%			0
墙面	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
地板	20%			20%			20%			20%			20%			0
室空间比	工 作 面 利 用 系 数															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	.00
1.0	1.13	1.12	1.10	1.11	1.10	1.08	1.07	1.06	1.05	1.04	1.03	1.02	1.00	.00	.99	.97
2.0	1.09	1.06	1.04	1.07	1.05	1.03	1.04	1.02	1.01	1.01	.00	.98	.99	.97	.96	.95
3.0	1.05	1.02	.99	1.04	1.01	.98	1.01	.99	.97	.99	.97	.95	.97	.95	.94	.93
4.0	1.02	.98	.95	1.01	.97	.95	.99	.96	.94	.97	.95	.93	.95	.93	.92	.91
5.0	.99	.95	.92	.98	.94	.92	.96	.93	.91	.95	.92	.90	.93	.91	.90	.89
6.0	.96	.92	.90	.95	.92	.89	.94	.91	.89	.93	.90	.88	.92	.89	.88	.87
7.0	.94	.90	.87	.93	.90	.87	.92	.89	.87	.91	.88	.86	.90	.88	.86	.85
8.0	.91	.88	.85	.91	.88	.85	.90	.87	.85	.89	.87	.85	.88	.86	.84	.83
9.0	.89	.86	.84	.89	.86	.83	.88	.85	.83	.88	.85	.83	.87	.84	.83	.82
10.0	.88	.84	.82	.87	.84	.82	.87	.84	.82	.86	.83	.81	.85	.83	.81	.80



C角度范围: 0度 - 360度
C角度间隔: 90.0度
测试速度: 快速
环境温度: 25.3℃
测试人员: Xie Bi
测试日期: 2024-09-03

γ角度范围: 0度 - 180度
γ角度间隔: 0.5度
测试系统: 远方 (EVERFINE) GO-2000A_V1系统 V2.00.417
环境湿度: 65.0%
测试距离: 6.810米 [K=1.0000]
备注:

墙面和天花板利用系数

实测参数: U:232.26V I:0.1799A P:22.347W PF:0.5349 Freq:49.99Hz 实检光通:1214.41x1 lm									
灯具名称: W2923LED					灯具类型:			灯具重量:	
灯具规格: P-W2923LED-3x7W2718-CI50012R90-YML100					外型尺寸:			测试编号:	
制造厂商:					发光口面:			遮光角:	

顶棚	80%			70%			50%			30%			10%			0
墙面	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
地板	20%			20%			20%			20%			20%			0
室空间比	墙 壁 面 利 用 系 数															
0.0																
1.0	.124	.071	.022	.118	.067	.021	.105	.060	.019	.094	.054	.017	.083	.048	.016	
2.0	.114	.062	.019	.108	.060	.018	.098	.055	.017	.089	.050	.016	.080	.045	.014	
3.0	.105	.056	.017	.101	.054	.016	.092	.050	.015	.084	.046	.014	.077	.043	.013	
4.0	.098	.051	.015	.094	.049	.015	.087	.046	.014	.080	.043	.013	.074	.040	.012	
5.0	.092	.047	.014	.088	.045	.013	.082	.043	.013	.077	.040	.012	.071	.038	.011	
6.0	.086	.043	.012	.083	.042	.012	.078	.040	.012	.073	.038	.011	.069	.036	.011	
7.0	.081	.040	.011	.079	.039	.011	.075	.038	.011	.070	.036	.010	.066	.034	.010	
8.0	.077	.038	.011	.075	.037	.010	.071	.036	.010	.068	.034	.010	.064	.033	.010	
9.0	.073	.036	.010	.072	.035	.010	.068	.034	.010	.065	.033	.009	.062	.031	.009	
10.0	.070	.034	.009	.069	.033	.009	.066	.032	.009	.063	.031	.009	.060	.030	.009	

顶棚	80%			70%			50%			30%			10%			0
墙面	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
地板	20%			20%			20%			20%			20%			0
室空间比	天花板利用系数															
0.0	.193	.193	.193	.165	.165	.165	.113	.113	.113	.065	.065	.065	.021	.021	.021	
1.0	.170	.160	.152	.145	.138	.130	.099	.095	.090	.057	.055	.052	.018	.018	.017	
2.0	.151	.135	.122	.129	.116	.105	.089	.081	.074	.051	.047	.043	.016	.015	.014	
3.0	.135	.116	.100	.116	.100	.087	.080	.069	.061	.046	.040	.036	.015	.013	.012	
4.0	.122	.100	.083	.105	.087	.072	.072	.060	.051	.042	.035	.030	.013	.011	.010	
5.0	.111	.088	.070	.095	.076	.061	.066	.053	.043	.038	.031	.026	.012	.010	.008	
6.0	.102	.077	.060	.087	.067	.052	.060	.047	.037	.035	.028	.022	.011	.009	.007	
7.0	.094	.069	.052	.081	.060	.045	.056	.042	.032	.032	.025	.019	.010	.008	.006	
8.0	.087	.062	.045	.075	.054	.039	.052	.038	.028	.030	.022	.017	.010	.007	.006	
9.0	.081	.056	.040	.070	.049	.035	.048	.034	.025	.028	.020	.015	.009	.007	.005	
10.0	.076	.051	.035	.065	.045	.031	.045	.031	.022	.026	.019	.013	.009	.006	.004	

C角度范围: 0度 - 360度
C角度间隔: 90.0度
测试速度: 快速
环境温度:25.3℃
测试人员:Xie Bi
测试日期:2024-09-03

γ角度范围: 0度 - 180度
γ角度间隔: 0.5度
测试系统: 远方 (EVERFINE) GO-2000A_V1系统 V2.00.417
环境湿度:65.0%
测试距离:6.810米 [K=1.0000]
备注:

UGR(Unified Glare Rating)数据表

实测参数: U:232.26V I:0.1799A P:22.347W PF:0.5349 Freq:49.99Hz 实检光通:1214.41x1 lm										
灯具名称: W2923LED					灯具类型:			灯具重量:		
灯具规格: P-W2923LED-3x7W2718-CI50012R90-YML100					外型尺寸:			测试编号:		
制造厂商:					发光口面:			遮光角:		
反射比: 天花板	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
墙面	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
工作面	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
房间尺寸	交叉 (Viewed crosswise)					向前 (Viewed endwise)				
x = 2H y = 2H	0.2	0.8	0.4	0.9	1.1	-0.2	0.4	0.0	0.5	0.7
3H	0.1	0.6	0.3	0.8	1.0	-0.3	0.2	-0.1	0.4	0.6
4H	0.0	0.5	0.3	0.7	0.9	-0.4	0.1	-0.1	0.3	0.5
6H	-0.1	0.4	0.2	0.6	0.9	-0.5	0.0	-0.2	0.2	0.5
8H	-0.1	0.4	0.2	0.6	0.9	-0.5	-0.1	-0.2	0.2	0.4
12H	-0.2	0.3	0.2	0.6	0.8	-0.6	-0.1	-0.3	0.1	0.4
4H 2H	0.0	0.5	0.3	0.7	1.0	-0.4	0.1	-0.1	0.3	0.5
3H	-0.1	0.3	0.2	0.6	0.8	-0.5	-0.1	-0.2	0.2	0.4
4H	-0.2	0.2	0.1	0.5	0.8	-0.6	-0.2	-0.3	0.1	0.4
6H	-0.3	0.0	0.0	0.4	0.7	-0.7	-0.4	-0.4	-0.1	0.3
8H	-0.4	-0.1	-0.0	0.3	0.7	-0.8	-0.5	-0.4	-0.1	0.3
12H	-0.5	-0.1	-0.0	0.2	0.6	-0.9	-0.5	-0.5	-0.2	0.2
8H 4H	-0.4	-0.1	-0.0	0.3	0.7	-0.8	-0.5	-0.4	-0.1	0.3
6H	-0.5	-0.2	-0.1	0.2	0.6	-0.9	-0.6	-0.5	-0.2	0.2
8H	-0.6	-0.3	-0.1	0.1	0.5	-1.0	-0.7	-0.5	-0.3	0.1
12H	-0.6	-0.4	-0.2	0.0	0.5	-1.1	-0.8	-0.6	-0.4	0.1
12H 4H	-0.5	-0.1	-0.0	0.2	0.6	-0.9	-0.5	-0.5	-0.2	0.2
6H	-0.6	-0.3	-0.1	0.1	0.5	-1.0	-0.7	-0.5	-0.3	0.1
8H	-0.6	-0.4	-0.2	0.0	0.5	-1.1	-0.8	-0.6	-0.4	0.1
不同间隔布灯时,观察者位置引起的UGR变化:										
S = 1.0H	+ 3.4 / -10.5					+ 3.2 / -11.9				
1.5H	+ 5.2 / - 7.6					+ 4.9 / - 7.7				
2.0H	+ 5.9 / -13.0					+ 5.3 / -17.1				

依据CIE Pub.117计算, 1214lm光源光通表格中的数据需要进行修正($81\log(F/F_0) = 0.7$)。
出光口面积: 0.0092 m²

C角度范围: 0度 - 360度
C角度间隔: 90.0度
测试速度: 快速
环境温度: 25.3℃
测试人员: Xie Bi
测试日期: 2024-09-03

γ角度范围: 0度 - 180度
γ角度间隔: 0.5度
测试系统: 远方 (EVERFINE) GO-2000A_V1系统 V2.00.417
环境湿度: 65.0%
测试距离: 6.810米 [K=1.0000]
备注:

UF利用系数表

实测参数: U:232.26V I:0.1799A P:22.347W PF:0.5349 Freq:49.99Hz 实检光通:1214.41x1 lm		
灯具名称: W2923LED	灯具类型:	灯具重量:
灯具规格: P-W2923LED-3x7W2718-CI50012R90-YML100	外型尺寸:	测试编号:
制造厂商:	发光口面:	遮光角:


反 射 比 / REFLECTANCE										
天花板	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
墙壁	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
工作面	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
室形指数	利用系数 UTILIZATION FACTORS(%) k(RI) x RCR = 5									
k = 0.60	91	85	82	90	85	82	90	85	82	78
0.80	98	93	89	97	92	89	96	92	89	86
1.00	102	97	93	101	96	93	99	96	93	89
1.25	105	101	97	104	100	97	102	99	96	92
1.50	108	103	100	106	103	100	104	101	99	95
2.00	110	106	103	108	105	102	106	103	101	96
2.50	111	108	105	110	107	104	107	104	102	96
3.00	113	110	107	111	108	106	107	105	104	97
4.00	114	112	110	112	110	109	109	107	106	99
5.00	116	114	112	113	112	110	110	108	107	100
ROOM INDEX	UF (总)									UF (直接)
依据标准文件 DIN EN 13032-2 2004			悬挂灯				安装距高比 SHRNOM = 1.25			

C角度范围: 0度 - 360度
C角度间隔: 90.0度
测试速度: 快速
环境温度:25.3℃
测试人员:Xie Bi
测试日期:2024-09-03

γ角度范围: 0度 - 180度
γ角度间隔: 0.5度
测试系统: 远方 (EVERFINE) GO-2000A_V1系统 V2.00.417
环境湿度:65.0%
测试距离:6.810米 [K=1.0000]
备注:

灯具等光强曲线

实测参数: U:232.26V I:0.1799A P:22.347W PF:0.5349 Freq:49.99Hz 实检光通:1214.41x1 lm		
灯具名称: W2923LED	灯具类型:	灯具重量:
灯具规格: P-W2923LED-3x7W2718-CI50012R90-YML100	外型尺寸:	测试编号:
制造厂商:	发光口面:	遮光角:




C角度范围: 0度 - 360度
C角度间隔: 90.0度
测试速度: 快速
环境温度: 25.3℃
测试人员: Xie Bi
测试日期: 2024-09-03

γ角度范围: 0度 - 180度
γ角度间隔: 0.5度
测试系统: 远方 (EVERFINE) GO-2000A_V1系统 V2.00.417
环境湿度: 65.0%
测试距离: 6.810米 [K=1.0000]
备注:

灯具有效平均照度图

实测参数: U:232.26V I:0.1799A P:22.347W PF:0.5349 Freq:49.99Hz 实检光通:1214.41x1 lm		
灯具名称: W2923LED	灯具类型:	灯具重量:
灯具规格: P-W2923LED-3x7W2718-CI50012R90-YML100	外型尺寸:	测试编号:
制造厂商:	发光口面:	遮光角:

光通输出:587.7 lm




注:曲线为灯具在不同投射距离下的照射区域及区域内平均照度。

C角度范围: 0度 - 360度
C角度间隔: 90.0度
测试速度: 快速
环境温度:25.3℃
测试人员:Xie Bi
测试日期:2024-09-03

γ角度范围: 0度 - 180度
γ角度间隔: 0.5度
测试系统: 远方 (EVERFINE) GO-2000A_V1系统 V2.00.417
环境湿度:65.0%
测试距离:6.810米 [K=1.0000]
备注:

平面等照度曲线

实测参数: U:232.26V I:0.1799A P:22.347W PF:0.5349 Freq:49.99Hz 实检光通:1214.41x1 lm		
灯具名称: W2923LED	灯具类型:	灯具重量:
灯具规格: P-W2923LED-3x7W2718-CI50012R90-YML100	外型尺寸:	测试编号:
制造厂商:	发光口面:	遮光角:



C角度范围: 0度 - 360度
C角度间隔: 90.0度
测试速度: 快速
环境温度: 25.3℃
测试人员: Xie Bi
测试日期: 2024-09-03

Y角度范围: 0度 - 180度
Y角度间隔: 0.5度
测试系统: 远方 (EVERFINE) GO-2000A_V1系统 V2.00.417
环境湿度: 65.0%
测试距离: 6.810米 [K=1.0000]
备注:

LED筒灯平均亮度报告

实测参数: U:232.26V I:0.1799A P:22.347W PF:0.5349 Freq:49.99Hz 实检光通:1214.41x1 lm		
灯具名称: W2923LED	灯具类型:	灯具重量:
灯具规格: P-W2923LED-3x7W2718-CI50012R90-YML100	外型尺寸:	测试编号:
制造厂商:	发光口面:	遮光角:


平均亮度	数值 (cd/m2)
L横 (65) av	36
L横 (75) av	0
L横 (85) av	0
L纵 (65) av	13
L纵 (75) av	0
L纵 (85) av	0
L45 (65) av	21
L45 (75) av	0
L45 (85) av	0

注:依据标准 GB/T 29293-2012 计算

C角度范围: 0度 - 360度
C角度间隔: 90.0度
测试速度: 快速
环境温度:25.3℃
测试人员:Xie Bi
测试日期:2024-09-03

γ角度范围: 0度 - 180度
γ角度间隔: 0.5度
测试系统: 远方 (EVERFINE) GO-2000A_V1系统 V2.00.417
环境湿度:65.0%
测试距离:6.810米 [K=1.0000]
备注:

平面照度曲线



C角度范围: 0度 - 360度
C角度间隔: 90.0度
测试速度: 快速
环境温度: 25.3℃
测试人员: Xie Bi
测试日期: 2024-09-03

γ角度范围: 0度 - 180度
γ角度间隔: 0.5度
测试系统: 远方 (EVERFINE) GO-2000A_V1系统 V2.00.417
环境湿度: 65.0%
测试距离: 6.810米 [K=1.0000]
备注:

光强分布数据表格

实测参数: U:232.26V I:0.1799A P:22.347W PF:0.5349 Freq:49.99Hz 实检光通:1214.41x1 lm		
灯具名称: W2923LED	灯具类型:	灯具重量:
灯具规格: P-W2923LED-3x7W2718-CI50012R90-YML100	外型尺寸:	测试编号:
制造厂商:	发光口面:	遮光角:

表--1

单位: cd

C (DEG) γ (DEG)	0	90	180	270															
0	8680	8679	8680	8679															
5	7310	6926	7170	7452															
10	4335	3872	4204	4438															
15	1850	1608	1802	1951															
20	540	455	532	581															
25	144	130	139	150															
30	65.5	62.0	63.7	67.1															
35	35.4	32.0	33.6	36.9															
40	17.2	14.7	16.1	17.9															
45	8.49	6.90	7.96	8.75															
50	4.24	4.02	4.42	5.32															
55	2.03	1.48	2.00	2.54															
60	0.72	0.51	0.66	0.89															
65	0.16	0.00	0.12	0.10															
70	0.00	0.00	0.00	0.00															
75	0.00	0.00	0.00	0.00															
80	0.00	0.00	0.00	0.00															
85	0.00	0.00	0.00	0.00															
90	0.00	0.00	0.00	0.00															
95	0.00	0.00	0.00	0.00															
100	0.00	0.00	0.00	0.00															
105	0.00	0.00	0.00	0.00															
110	0.00	0.00	0.00	0.00															
115	0.00	0.00	0.00	0.00															
120	0.00	0.00	0.01	0.01															
125	0.00	0.00	0.02	0.02															
130	0.01	0.02	0.04	0.03															
135	0.06	0.09	0.06	0.06															
140	0.22	0.31	0.11	0.11															
145	0.72	0.91	0.28	0.28															
150	1.87	2.13	0.78	0.76															
155	3.71	3.94	1.87	1.80															
160	5.73	5.79	3.50	3.35															
165	6.86	6.87	5.04	4.85															
170	6.64	6.80	5.70	5.61															
175	5.79	6.11	5.54	5.58															
180	5.55	5.74	5.54	5.74															

C角度范围: 0度 - 360度

C角度间隔: 90.0度

测试速度: 快速

环境温度: 25.3℃

测试人员: Xie Bi

测试日期: 2024-09-03

γ角度范围: 0度 - 180度

γ角度间隔: 0.5度

测试系统: 远方(EVERFINE)GO-2000A_V1系统 V2.00.417

环境湿度: 65.0%

测试距离: 6.810米 [K=1.0000]

备注: